

T-2R HIGH PERFORMANCE 2-STROKE OIL

>>Description

T-2R High Performance 2-Stroke Oil is designed for today's High Performance Recreational Machines. T-2R's well-balanced blend of smokeless synthetic and highly refined petroleum base oils provides extra wear protection, "ultra clean" performance, enhanced throttle response and increased horsepower. T-2R has an advanced additive system minimizes spark plug fouling and ring sticking under a full range of RPM and temperature.



>>Features

- >Synthetic blend technology
- >Most advanced smokeless performance
- >Improves power efficiency and throttle response
- >Provides superior detergency for clean, deposit free operation

>>Application

For use in small air cooled and liquid cooled 2-cycle engines: motorcycle, scooter, ATV and other similar applications. Designed for oil injection systems but can also be used in premix applications. Exceeds all manufacturer warranty requirements. Exceeds: JASO-FC / ISO-L-EGD

>>Typical/Test Data

Description	ASTM#	T-2R
Appearance	Visual	CL/Red
Viscosity @ 100°C	D-445	8.41
Viscosity @ 40°C	D-445	58.5
Pour Point, °C	D-97	-35
Flash Point, °C	D-92	73

>>Directions

Use at full strength in injector systems. For best performance in premix applications, T-2R is recommended at a ratio of 40:1.

>>Package Sizes / P/N

Description	T-2R
500mL Bottle	T920033YE
Case 12/1 500mL	T920033Y
5 Gallon Pails	T920033E
55 Gallon Drum	T920033B