



# TECHNICAL DATA

PRODUCT TECH

©2010 TORCO

## ATV SPORT 4-STROKE RACING OIL

SAE 15W/40

### >>Description

Torco ATV Sport 4-Stroke Racing Oil is a blend of specially selected synthetic and petroleum base oils for off-road four-stroke racing engines. Under typical conditions these engines use lower oil volumes, run at elevated engine temperatures, higher RPM's, severe shock loads and endure active clutch use. Due to these conditions, ATV Sport was designed with high V.I. base oils and unique polymers to provide extreme thermal and shear stability. Special additive systems improve ring seal, protect valve train, eliminate deposits, control foam, and provide smooth, positive clutch activation. ATV Sport provides unmatched shock load and extreme pressure protection for integrated transmissions.

### >>Features

- >Synthetic blend technology
- >Low friction modified
- >Off-road specific formula
- >Improves ring seal and shifting
- >Provides smooth, positive clutch activation
- >Superior anti-wear and deposit-free performance

### >>Application

ATV Sport is recommended for use in air cooled or liquid cooled four-stroke stock and racing engines where an SAE 10W30, 10W40, 15W40, 15W50, 20W40, and 20W50 are specified. Commonly used in Honda®, Kawasaki®, Suzuki®, Yamaha®, KTM®, Can Am®, Polaris®, and other four-stroke ATV applications.

Exceeds manufacturer warranty requirements. Exceeds API SG / JASO-MA. CCMC G4/G5\* ACEA A3-96

### >>Typical/Test Data

<b>SAE Grade</b>	<b>ASTM#</b>	15W/40
<b>Appearance</b>	<b>Visual</b>	Amber
<b>API Gravity</b>	<b>D-287</b>	30.7
<b>Lbs/Gal</b>	<b>Tables</b>	7.264
<b>Specific Gravity @ 15.6/15.6°C</b>	<b>D-1298</b>	0.8724
<b>Viscosity @ 100°C</b>	<b>D-445</b>	16.1
<b>Viscosity @ 40°C</b>	<b>D-445</b>	116.28
<b>Viscosity Index</b>	<b>D-2270</b>	136
<b>Pour Point, °C</b>	<b>D-97</b>	-18
<b>Flash Point, °C</b>	<b>D-92</b>	236
<b>Fire Point, °C</b>	<b>D-92</b>	246
<b>TBN</b>	<b>D-2896</b>	5.7
<b>CCS Viscosity, cP @ °C</b>	<b>D-2602</b>	6631 @ -20

### >>Directions

Follow manufacturer's fill level requirements. Compatible with other petroleum and synthetic lubricants.

### >>Package Sizes / P/N

<b>SAE Grade</b>	15W/40
<b>1-Liter (1.056 US QT)</b>	T691540CE
<b>12/1-Liter Case</b>	T691540C
<b>5 Gallon Pail</b>	T691540E
<b>55 Gallon Drum</b>	T691540B

TORCO INTERNATIONAL CORPORATION  
9145 Milliken Avenue, Rancho Cucamonga, CA 91730  
(909) 980.1495 phone | (909) 980.1465 fax  
www.torcousa.com website | [info@torcousa.com](mailto:info@torcousa.com) email